



MONOLITHIC SIDEWALK/CURB

NOTES:

1. BROOM FINISH FOR ALL EXPOSED SURFACES.
2. CONCRETE SHALL BE ODOT CLASS "C", 6% AIR, #57 LIMESTONE AGGREGATE.
3. ALL EXPOSED SURFACES RECEIVE 2" EDGING (EXCEPT CURB).
4. SIDEWALK WIDTH DIMENSION VARIES PER PLAN, PER EXISTING SIDEWALK, OR AS DIRECTED BY THE ENGINEER. TYPICALLY, 4' FOR 50' R/W OR LESS AND 5' FOR 50' R/W AND GREATER. MONOLITHIC SIDEWALK/CURB SHALL BE PER PLAN OR REPLACEMENT OF EXISTING.
5. SIDEWALK THRU RESIDENTIAL DRIVE 6" MIN. THICKNESS. SIDEWALK THRU COMMERCIAL DRIVE 8" MIN. ALL OTHER SIDEWALK 4" MIN.
6. 4" MIN GRANULAR BASE FOR NEW SIDEWALK. GRANULAR BASE FOR REPLACEMENT SIDEWALK AS DIRECTED BY ENGINEER.



ENGINEERING DIVISION
 44 W. HEBBLE AVENUE FAIRBORN, OHIO 45324
 PH: (937) 754-3055 FX: (937) 879-7395

SIDEWALK DETAIL

NOTE 1: DRAWING VALID ONLY WHEN USED AS SHOWN AND IN CONJUNCTION WITH OTHER FAIRBORN ENGINEERING SPECIFICATIONS AND/OR DETAILS. THIS DRAWING REPRESENTS MINIMUM STANDARDS. ANY MODIFICATIONS TO THIS DETAIL SHALL FIRST BE SUBMITTED TO THE CITY ENGINEER FOR APPROVAL.

NOTE 2: CALL THE FOLLOWING AGENCIES AT LEAST 48 HOURS IN ADVANCE OF ANY EXCAVATION:
 O.U.P.S. AT 8-1-1 AND O.A.G.P.U.P.S. AT (800) 925-0988

REV NO	REV DATE	REV DESCRIPTION	REV NO	REV DATE	REV DESCRIPTION

DWG NO:	PV-4.0
ISSUE DATE:	01/25/2019
ENGR:	MAJ
APPROVED:	TLH
SCALE:	NONE
FILE:	